

IMPORTANT: Read these instructions carefully before using the CAR VAC. Proper use and care of this unit will keep it in good condition and ensure trouble-free operation for years to come.

For your safety -

1. Do not use the Car Vac near your face.
2. Store unit in a safe place, away from children, when not in use.
3. Do not operate unit with filter bag removed.
4. Do not use on burning materials such as smoldering cigarette butts.
5. Do not run vehicle's engine while operating unit.
6. Keep fan area and collection bowl clear of foreign objects and clean filter frequently.
7. Do not operate in areas where flammable fumes are present.
8. It is safe to run the Car Vac for up to 1/2 hour at a time.
9. For proper storage, put the cord into the storage compartment (Fig. 1).

ON/OFF Operation

The unit is turned ON by sliding the ON/OFF switch forward (towards the nozzle end of the Car Vac), and turned OFF by sliding the switch backwards. The switch automatically locks in the ON position, thus making it unnecessary to depress any switches while cleaning.

Vacuuming Instructions

1. Securely push the vacuum plug into your 12 volt power source (such as vehicle cigarette lighter jack).
2. Slide the ON/OFF switch forward.
3. Clean the washable vacuum cleaner bag frequently to ensure most efficient vacuuming.
4. When cleaning high pile carpets, always pull the nozzle towards you (Fig. 2)
5. When vacuuming fluids, affix the rubber squeegee to the end of the canister.




Fig. 1




Fig. 2




Fig. 3

Using the Crevice Tool, Upholstery Tool
The crevice tool is used for cleaning hard-to-reach areas. The upholstery tool is for use on upholstered or carpeted areas. Simply insert the attachment into the open end (nozzle) of the vacuum (Fig. 3).

Cleaning the Collection Bowl and Filter Bag

1. To remove dirt from collection bowl hold unit as shown (Fig. 4).
2. Depress latch and swing collection bowl away and down from handle.
3. Pull filter bag from collection bowl (Fig. 5).
4. Empty dirt from collection bowl (Fig. 6).
5. To clean washable filter bag you can:
 - a. Brush the dirt from the bag (Fig. 6).
 - b. Shake the bag clean into a proper receptacle (Fig. 7).
 - c. Hand wash the bag with a mild detergent. Note: After washing, place a paper towel into the filter bag and squeeze the filter to absorb excess moisture. Be sure the filter bag is completely dry before reinserting it into the Car Vac (Fig. 8).
6. Reassemble collection bowl to the unit (Fig. 9) by aligning rear lower edge of collection bowl with lower front edge of unit, then snap the two parts together so that upper latch snaps in place.




Fig. 4




Fig. 5



Fig. 6




Fig. 7




Fig. 8




Fig. 9

Cleaning Plastic Parts

Use only mild soaps or a cloth dampened with hot water to clean the plastic parts. Avoid strong detergents or caustic cleaners which can damage the Car Vac.